



Washdown Portion Weigher Topping Scale
 • UL Approved



Features & Benefits

- HI/OK/LO indicators with configurable buzzer output ideal for portion control or checkweighing
- Washdown design to IP 66 Can be used in wet conditions
- Heavy duty construction Will withstand harsh industrial operation
- Fast reaction time Allows fast throughput
- Sealed electronics Improved water and dust resistance
- Moisture detection desiccant inside Alerts to moisture inside scale
- Low profile, compact size Uses less counter space
- Reads in grams, pounds and pounds: ounces Flexibility of operation
- Built-in rechargeable battery or external power adaptor
- Portability - battery lasts a minimum of 80 hours
- Zero tracking Assures that you always start weighing at zero
- Automatic power save / standby indicator Conserves battery power
- Low battery indicator / charge status indicator
- Alerts you to charge the battery, saving downtime
- Auto-calibration function Ensures accuracy
- Adjustable feet Balance remains level for accurate results on uneven working surfaces - Anti-slip
- LED display Can be read even in poor lighting conditions

Model	DW-3000E	DW-6000E	DW-15KE	DW-30KE
Capacity	3,000 g / 6 lb	6,000 g / 12 lb	15 kg / 33 lb	30 kg / 66 lb
Readability	1 g / 0.002 lb	2 g / 0.005 lb	0.005 kg / 0.01 lb	0.01 kg / 0.02 lb
Divisions	3,000	3,000	3,000	3,000
Weighing Units / Functions	g / lb / lb : oz			
Stabilization Time (seconds)	< 1.5			
Tare Range	To capacity by subtraction			
Power Source	Built-in rechargeable battery or external power adaptor (included)			
Construction	Stainless steel pan and water resistant ABS housing			
Display	0.75 inches (19 mm) wide viewing angle LED			
Pan Size (w x d)	9.84 x 8.46 inches (250 x 215 mm)			
Dimensions (w x h x d)	10.62 x 5.7 x 10.9 inches (270 x 145 x 278 mm)			
Operating Environment	32° ~ 104° F non condensing R.H. ≤ 95%			
Net Weight	8.15 lb (3.7 kg)			
Shipping Weight	11 lb (5 kg)			
IP rating / Approvals	IP 66 / UL Approved (Special Equipment and/or Devices, Sanitation)			
Options	RS232C interface, Secondary rear panel mount display			