



JW

SERIES

HIGH PRECISION BALANCE



FEATURES

- 1/50000 Display Resolution
- 24 Bit Σ - Δ High Speed A/D Converter with over 1,000,000 Internal Count
- Ideal for Laboratory and Jewelry Shops
- 6 x 19mm + 3 x 10mm Bold Type Wide Angle LCD Display Digits
- 13 User Programmable Weighing Units:- Metric, Metric Carat, Pound, Ounce, Dram, Grain (U.K.), Troy Ounce, Pennyweight, Momme (Japan), Tael (Taiwan), Tael (China), Troy Tael, Tola (India)
- User Friendly Operation
- Equipped with Initial Zero Tracking, Manual Zero Setting, Percentage Weighing, Counting Function, Smart Power Saving and Auto Calibration
- Dual Power Sources: Built-in Rechargeable Battery or Power Adaptor
- Long Battery Operating Time: 100 Hours Plus
- Low Battery Warning Signal
- See-through Easy Assemble Wind Shield
- Adjustable Feet, Backlight, Bubble Level, Protection Cover, AC/DC Power Adaptor, RS232C Interface, Wind Shield (JW-250, JW-500 & JW-1000 only) and Stainless Steel Platter Included

SPECIFICATIONS

Model No.	JW-250	JW-500	JW-1000	JW-2500
Capacity	250g	500g	1000g	2500g
Readability	0.005g	0.01g	0.02g	0.05g
Repeatability (Std. dev.)	0.005g	0.01g	0.02g	0.05g
Pan Size	Ø110mm		140x170mm	
Wind Shield	YES		NO	
Tare Range	Full Tare Range (Subtractive)			
Power Source	By Built-in Rechargeable Battery or External Power Adaptor			
Operating Environment	10° ~ 35°C / 50° ~ 95° F Non-condensed. R.H. ≤ 85%			
Individual Package	310 X 310 X 230mm			
Net/Gross Weight	1.8kg/2.9kg (JW-500, 1000, 1500) 2.2kg/3.3kg (JW-2500)			

• Specifications subject to change without notice

