

# STAINLESS STEEL BENCH SCALES

EB-150 with  
210 Indicator



Designed for top  
performance and  
long-term accuracy.

## FEATURES:

- Stainless Steel Construction
- Large LED or LCD Display
- Push Button Tare
- Flexible Print Formats
- Pounds/Kilograms Conversion
- Gross, Tare, Net Conversion
- AC or Battery Power
- Auto Shutoff

EB-300 with  
210 Indicator



# Stainless steel bench scales . . . now with improved features to answer your needs

Simplicity of design and rugged construction are the key features of our new stainless steel bench scale series. A simple frame and bridge design with lift-off platform simplifies cleanup by providing direct access to all of the components.

Select the size and capacity scale you need and match it up with the Cardinal indicator that best suits your application. The 204 is perfect for basic weighing. For harsher environments choose the 205 with NEMA 4x enclosure or the 210 which also features keypad tare, piece count and checkweighing.

Whatever your needs may be, select from Cardinal's complete line of stainless steel bench scales.



EB-15  
with 205  
Indicator



EB-150  
with 204  
Indicator

## Specifications

### Display:

**Model 204:** 6-digit, 7-segment LCD, 25mm/1" high  
**Model 205/210:** 6-digit, 7-segment LED, 14mm/0.6" high

### Annunciators:

**Model 204:** Zero, gross, tare, net, low battery  
**Model 205:** Zero, gross, tare, net, low battery, stable, lb, oz, kg, g, t, T,  
**Model 210:** All of the above plus PWC-1/under, PWC-2/accept, PWC-3/over

### Enclosure:

**Model 204:** Stainless steel - 8"W x 6 5/8"H x 2 1/8"D  
204mm x 168mm x 54mm  
**Model 205/210:** NEMA 4X/IP66 - 9"W x 7"H x 2 3/4"D  
229mm x 178mm x 70mm

### Keyboard:

**Model 204/205:** 7 keys  
**Model 210:** 22 keys

### Units:

Pounds, kilograms, ounces, grams, or pounds/kilograms

### Sample Rate:

1 - 50 samples per second, selectable

### Auto Zero Range:

0.5 or 1 to 9 graduations

### Resolution:

1 part in 100,000 displayed

1 part in 1,000,000 internal

### Power:

90 to 260 VAC, 50 or 60 Hz

### Temperature Range:

-10°C to 40°C/14°F to 104°F

### I/O:

1 bidirectional RS232 (20mA)

1 output only RS232 (20mA)

The optional battery allows the indicator to be used anywhere, or to keep you weighing even during power outages.



Model	Capacity	Platform Size
EB-15-204	15 lb x .005 lb/6 kg x .002 kg	250 x 300 mm/10" x 12"
EB-15-205		
EB-15-210		
EB-15-LPAN		
EB-30-204	30 lb x .01 lb/15 kg x .005 kg	250 x 300 mm/10" x 12"
EB-30-205		
EB-30-210		
EB-30-LPAN		
EB-60-204	60 lb x .02 lb/30 kg x .01 kg	350 x 400 mm/14" x 16"
EB-60-205		
EB-60-210		
EB-60-LPAN		
EB-150-204	150 lb x .05 lb/60 kg x .02 kg	350 x 400 mm/14" x 16"
EB-150-205		
EB-150-210		
EB-150-LPAN		
EB-300-204	300 lb x .1 lb/150kg x .05 kg	500 x 600 mm/20" x 24"
EB-300-205		
EB-300-210		
EB-300-LPAN		



03-031



Cardinal Scale reserves the right to improve, enhance, and modify features and specifications without prior notice.

Sold By:



**Universal  
Scale  
Service**

7980 Mill Station Rd  
Sebastopol, CA 95472  
Ph : (707) 829-8482  
(800) 578-7948  
Fx : (707) 829-3925