

Triple Range Counting Scale

- High Precision Counting



| Model | SAC-7.5 C | SAC-15 C | SAC-30 C | SAC-60 C |
|-------------------------------------|--|------------------|------------------|------------------|
| 1st Interval Capacity / Readability | 3 lb / 0.0002 lb | 5 lb / 0.0005 lb | 10 lb / 0.001 lb | 30 lb / 0.002 lb |
| 2nd Interval Capacity / Readability | 7.5 lb / 0.0005 lb | 15 lb / 0.001 lb | 30 lb / 0.002 lb | 75 lb / 0.005 lb |
| 3rd Interval Capacity / Readability | 15 lb / 0.001 lb | 30 lb / 0.002 lb | 60 lb / 0.005 lb | 150 lb / 0.01 lb |
| Maximum Division | 75,000 | 75,000 | 75,000 | 75,000 |
| Internal Counting Resolution | 1,000,000 counts | | | |
| Weighing Unit / Function | lb / counting | | | |
| Stabilization Time (seconds) | < 1.5 | | | |
| Tare Range | To capacity by subtraction | | | |
| Power Source | Built-in rechargeable battery or external power adaptor (included) | | | |
| Construction | Stainless steel pan and ABS housing | | | |
| Display | 0.6 inches (15 mm) wide viewing angle LCD | | | |
| Pan Size (w x d) | 13.6 x 9 inches / 345 x 230 mm | | | |
| Dimensions (w x h x d) | 14.2 x 4.5 x 14.2 inches / 360 x 114 x 360 mm | | | |
| Operating Environment | 32° ~ 104° F non condensing R.H. ≤ 85% | | | |
| Net Weight | 10.4 lb / 4.7 kg | | | |
| Shipping Weight | 13 lb / 5.9 kg | | | |
| Options | RS 232 C interface or printer interface output | | | |

Features

- Heavy duty construction
- Low profile, compact size
- Built-in rechargeable battery or external power adaptor
- Zero tracking
- Automatic power save
- Low battery indicator / charge status indicator
- Auto-calibration function
- Adjustable feet and spirit level
- Wide angle LCD display with backlight

Benefits

- Will withstand harsh industrial operation
- Uses less counter space
- Portability - battery lasts a minimum of 100 hours (without back light)
- Assures that you always start weighing at zero
- Conserves battery power
- Alerts you to charge the battery, saving downtime
- Ensures accuracy
- Balance remains level for accurate results on uneven working surfaces - anti-slip
- Can be seen from a wide viewing angle

The SAC is equipped with the following state of the art counting features :

- Triple interval weighing range
- 24 Bit Σ - Δ high speed A/D converter
- Accumulation memory for weight and total count
- Full numeric keypad
- Over weighing and counting alarm
- 8 x one touch piece weight PLU
- Insufficient unit piece weight and sample size warning
- Auto piece weight enhancement

- Gives the ability to sample at low range, high accuracy and count at high capacity on the same scale
- Fast stabilization time. Increased accuracy
- Gives ability to add together weighings, either by count and weight
- User friendly operation & fast data entry
- Ensures fast throughput with less mistakes
- Frequently used component sample weights can be stored for easy retrieval
- Ensures correct sampling procedure
- Allows for finer counting



SOLD BY:



**Universal
Scale
Service**

7980 Mill Station Rd
Sebastopol, CA 95472
Ph : (707) 829-8482
(800) 578-7948
Fx : (707) 829-3925

Fast Affordable Quality Repairs