

200 Series

Digital Indicator



200 Series Digital Indicator



Features

Divisions— NTEP approved for 5,000 Divisions.

Serial Port— Full duplex RS-232 Serial Port.

Displays— Up to 50,000 Graduations.

Digital Calibration— Full front panel calibration.

Construction— Stainless steel swivel stand

Power Requirements— Operates on AC Adapter or 12 Volt DC.

S200— LCD Display

S200E— LED Display

Specifications

Enclosure— ABS NEMA 12 Enclosure.

Load Cell Excitation— +10 VDC

Load Cells— Drives up to four 350 Load Cells.

Load Cell Current— Drives up to four 350 Load Cells.

Analog Signal Input Range— 0.2 mV/V min to 3.0 mV/V max.

Analog Sensitivity— 0.4 μ V/grad, minimum.

1.0 μ V/grad recommended
minimum for Legal-for-Trade

A/D Conversion Rate— Up to 25 meas/sec.

A/D Resolution— Up to 260,000 Internal Counts.

Display— 0.6", 6 Digit Display.

Display Resolution— Up to 50,000 External Grads, Selectable.

Keyboard Functions— Units, Zero, Net/Gross, Tare, Print.

Annunciators— Gross, Net, kg, lb, Center of Zero, Stable, Tare, Negative, PCS.

Serial Port— Full Duplex RS-232 Format.

Power Requirement— 12 VDC, 500 mA Wall Adapter,



200 Series Digital Indicator

Features

- Serial Port— Full duplex RS-232 Serial Port.**
- Digital Calibration— Full front panel calibration.**
- Construction— Stainless steel swivel stand**
- Power Requirements— Operates on AC Adapter or 12 Volt DC.**
- S200— LCD Display**
- S200E— LED Display**

Specifications

- Load Cell Excitation— +10 VDC**
- Load Cell Current— Drives up to four 350 Load Cells.**
- Analog Signal Input Range— 0.2 mV/V min to 3.0 mV/V max.**
- Analog Sensitivity— 0.4 μ V/grad, minimum.**
1.0 μ V/grad recommended
minimum for Legal-for-Trade
- A/D Conversion Rate— Up to 25 meas/sec.**
- A/D Resolution— Up to 260,000 Internal Counts.**
- Display— 0.6", 6 Digit Display.**
- Display Resolution— Up to 50,000 External Grads, Selectable.**
- Keyboard Functions— Units, Zero, Net/Gross, Tare, Print.**
- Annunciators— Gross, Net, kg, lb, Center of Zero, Stable, Tare, Negative, PCS.**
- Serial Port— Full Duplex RS-232 Format.**
- Power Requirement— 12 VDC, 500 mA Wall Adapter, included.**
- Indicator Dimensions— 3.2" x 6.8" x 2.3"**
- Operating Temperature— 14° F to 104° F**
(-10°C to 40° C)

SOLD BY:



**Universal
Scale
Service**
7980 Mill Station Rd
Sebastopol, CA 95472
Ph : (707) 829-8482
(800) 578-7948
Fx : (707) 829-3925

Fast Affordable Quality Repairs