



Products Name

▶ W20

Model No.

▶ W20

Capacity

▶ Free setting

Division

▶ Free setting

Resolution

▶ 1/ 30000

Feature

- All Stainless Steel Housing
- Wash Down Design According to IP65
- Up to 1/ 30000 Display Resolution
- User Friendly Setup, Calibration and Operation Procedures
- Programmable Capacity, Display Resolution, Decimal Position, Zero Range, Zero Tracking Range/ Speed and Motion Detection Range for Various Applications and Environments
- Programmable Computer and Printer Output Transmission and Data Format
- Maximum Number of Load Cells Connected = 8 x 350Ω
- Weighing Unit Selectable: Metric Ton, Kilogram, Pound and Gram
- Tact-Switch Keyboard
- Equipped with Memory Function,

Motion Indicating Device

- Password Function to Prevent Unauthorized Access
- User Friendly Operation
- Dual Power Sources: Built-in Rechargeable Battery or Power Adaptor
- Low Battery Warning Signal
- Table Stand, Backlight and Built-in Rechargeable Battery are Included

SPECIFICATIONS

- 24 Bit Σ - Δ High Speed A/ D Converter with over 1, 000, 000 Internal Count
- Maximum Display Resolution: 1/ 30000
- Minimum Input per Display Resolution: 0.1 μ V
- A/ D Conversion Rate: 50/ second
- Display Refresh Rate: 25/ second
- Span Adjustment: 0.6mV/ V to 4mV/ V Full Scale
- Zero Drift: <0.3 μ V/ $^{\circ}$ C
- Span Drift: 8ppm/ $^{\circ}$ C
- Non-Linearity: <0.0033% R.O.
- Load Cell Excitation: 5 Volts for up to 8 x 350 Ω Load Cell
- Power Supply: AC 110/ 230V \pm 10%, 50/ 60 Hz, Rechargeable Battery 6V, 4Ah
- Operating Temperature: 0 $^{\circ}$ C ~ 40 $^{\circ}$ C (32 $^{\circ}$ F ~ 104 $^{\circ}$ F)

· Operating Relative Humidity:
< 90% Non-condensing

OPTIONS AVAILABLE

- JB-65 Junction Box of Maximum
8 Load Cell Channel
- UWE OP-5L Remote Display
- Waterproof Bi-directional
RS232C Interface
- Printer Interface**

**Indicator is Not Waterproof if
Printer Interface is Installed

[Close Window](#)