

## Intercomp PW800™ Pallet Truck Scales



### Standard Features

- Fast, low-cost parts counting for taking inventory
- Count totalization up to 1,000,000 counts
- Accuracy of  $\pm 0.1\%$
- Tare: up to 100% of capacity
- Zero: up to 100% of capacity
- Units of measure: lb/kg
- 5000 lb capacity in one-pound increments
- Pushbutton print of gross, net, tare, total, and count total
- Displays gross, net, and tare weight
- Weight totalization up to 100,000 lb
- Adjustable baud rates from 75 to 9600
- Low-cost operation on 9 "D" cell batteries
- Quick verification of incoming/outgoing freight
- Instant check of truck loading by weight
- Large, easy-to-read 0.8" six-digit LED (Light Emitting Diode) display
- Adjustable display update/weight averaging
- Selectable AZT off, 0.6, 1, or 3 graduations
- Mild steel

Pallet Truck Scale

### Specifications

**CAPACITY:**

5000 lb (2500 kg)

**GRADUATION:**

1 lb (.5 kg)

**ACCURACY:**

$\pm 0.1\%$  of reading

**BATTERY LIFE:**

Up to 40 hours of continuous use

**BATTERIES:**

9 "D" size disposable alkaline dry cells or rechargeable nickel-cadmium cells

**CHARGE TIME:**

16 hours

**CHARGE:**

Charger/power transformer — 115/230 VAC

**LOW BATTERY SHUT-OFF:**

Unit automatically shuts off if batteries are low

**AUTO SHUT-OFF:**

Shuts off after up to 5 minutes of non-use (variable up to 30 min)

**DISPLAY:**

0.8 inch (20 mm) high — 5 1/2-digit Light Emitting Diode (LED)

**INDICATORS:**

Six (lb, kg, net, tare, total, count)

**CONTROL SWITCHES:**

Eight (on, off, set mode, print, tare, zero, lb/kg)

**HUMIDITY:**

10 to 95% non-condensing

**TEMPERATURE:**

OPERATING: -20°C to 60°C (-4°F to 140°F)

**FORK DIMENSIONS:**

**PW800-2748:** 48" x 27" x 2.9" (1219 mm x 686 mm x 74 mm)

**PW800-2148:** 48" x 21" x 2.9" (1219 mm x 533 mm x 74 mm)

**EST. SHIP WEIGHT:**

300 lbs (136 kg)

**WARRANTY:**

1-year limited warranty

### Intercomp PW800

PART #	MODEL	FORK SIZE	CAPACITY	EST. SHIP WEIGHT
43659	PW800-2748	48" x 27" x 2.9"	5000 lb	300 lb
43660	PW800-2148	48" x 21" x 2.9"	5000 lb	300 lb
<b>Options/Accessories</b>				
43946	RS-232 serial output			