

7815

Features & Benefits:

Accurate and Reliable – Ensures trouble-free performance. Easy to Use – Reduces operator training time.

Easy to Read – Six digit LCD internal display with large 1/2" characters.

Construction – Die-cast load bridge reduces overall scale deflection. Overload protection safeguards load cell and extends life.

Fast Digital Response – Speeds processing time.

Compact Low Profile Base – Fits easily into any operation and provides convenient mobility.

I/O Port – RS-232 bi-directional, configurable 1200-19,200 baud. Transmits weight and scale status whenever "W" command is sent by a host device.

Calibration – Alternate span points can simplify field calibration by using less than full capacity weights.

Compatibility – Compatible with most shipping software programs, including UPS Worldship®.

RS-232 Cable – 10 ft. (3 meters) pass through cable with DB9-pin female connector at PC end.



Options:

Stainless Steel Weigh Platter – Durably constructed.

Ball-top Weigh Platter – Simplifies transport of all parcels.

Remote Display – Six digit LCD housed in a molded enclosure, 5.46" W x 2.26" H x 1" D with a 7 ft. cable.

Display Tower – 12" pole for remote display.

Specifications:

Capacity/Resolution:

150 lb x 0.1 lb "Legal for Trade"

150 lb x 0.05 lb "Not Legal for Trade"

Note: Standard configuration as weight classifier. Can be reconfigured for normal scale rounding in setup.

Construction:

ABS plastic weigh platter. Painted die cast aluminum base.

Controls:

ZERO - With auto zero tracking for zeroing the scale.

TEST - Runs a diagnostic program to ensure scale is fully functional or to view configuration.

Power:

120 VAC (+10% -15%)/60 Hz, standard 3-wire ground.

Operating environment:

42°F to 104°F (5°C to 40°C), 10% to 95%, RH (non-condensing).

Agency Approvals:

NIST Handbook 44 Class III, Commercial Applications (NTEP COC#00-096).

Shipping Weight:

21 lbs (standard configuration)

DIM Weight:

26 lbs (standard configuration)

SOLD BY:



**Universal
Scale
Service**

7980 Mill Station Rd
Sebastopol, CA 95472
Ph : (707) 829-8482
(800) 578-7948
fx : (707) 829-3925

Fast Affordable Quality Repairs